



SUBSCRIBE

Search

RSS | Blogs | Forums | Register | Sign In

NEWS STATS NEW PRODUCTS FEATURES COLUMNS BLOGS FORUMS PRODUCT GUIDES EVENTS RESI INTERNATIONAL

## Tributaries Expands AC Power Products Lineup

By RS Staff, September 23, 2011

[Tweet](#) 0 
 [Share](#)
[Like](#) Confirm 
 [You like this.](#)
[Admin Page](#)
[Insights](#)
[Error](#)
[You like this](#) Sign Up to see what your friends like. 
 [Admin Page](#)
[Insights](#)
[Error](#)

STORY TOOL BOX [print](#) [ShareThis](#) [rss](#) [Order a reprint](#)

Tributaries has made a new addition to its line of AC Power products with the PWRI-XF In-wall AC Power Extension Outlet Kit.

Engineered to work in conjunction with T100 and T200 Power Managers, the dual-outlet XF model provides remote protection and filtering for displays and projections.

The PWRI-XF AC Power Extension Outlet Kit contains three main parts:

- \* A dual AC outlet with filtering built into a housing that is designed to fit in a dual gang Carlon or Raco box finished with an integral plastic faceplate including a "POWER" LED, for installation behind the TV or projector.

- \* A Neutrik 120V/20A UL rated AC PowerCon inlet mounted on a single-gang white Decora wall plate for installation close to the T100/T200 Power Manager.

- \* A 14AWG shielded AC Power Cable with a Neutrik PowerCon AC plug on one end and a Nema 5-15, 3-prong straight or right angle AC plug on the other end.



The PWRI-XF AC Power Extension Outlet Kit.

With the installation of the PWRI-XF Kit, a TV or projector that is located at a distance from source components can be connected to a T100 or T200 Power Manager, taking advantage of its surge suppression and filtering capability. The extra filtering in the PWRI-XF outlet box that would be located behind the TV or projector, provides a second level of protection from EMI/RFI that could be induced into the unshielded in-wall wiring connecting the outlet box to the Neutrik inlet.

The PWRI-XF AC Power Extension Kit provides components with a clean source of power, free of signal degrading noise and distortion. The new model is designed to provide a maximum of 1800W/120V/15A of clean and filtered power to components.

Both inlet and outlet offer key points for safety and installation ease, with two UL ratings, ability to fit dual- or single-gang wall boxes, and connection via 14AWG Romex building wire. Kits are available in multiple configurations: 6-foot, 9-foot or 12-foot, AC power cable terminated with a Twist-Lock Neutrik PowerCon connector, with the Neutrik Twist-Lock PowerCon inlet.

In support of environmental protection, the PWRI-XF is RoHS compliant and also complies with the RoHS provision of California SB 20: Electronic Waste Recycling Act of 2003.

The PWRI-XF is now available, with SRP of \$160-180 depending on configuration.

The Integration Guide to **Retrofit** From the editors of Residential Systems

CRESTRON ELAN Gefen iLectouch nexus NILES

Residential Systems Digital Edition

Click [here](#) to read the latest issue now

From the editors of Residential Systems

The Integration Guide to **HDMI**

Click [here](#) to learn more

SPONSORED BY ACCELL DVIGEAR Gefen Liberty QVS

Residential Systems Newsletters

Click [here](#) to start your FREE subscriptions

The Latest Information Sent Right To Your Desktop

### RELATED ARTICLES

- Tributaries Best Overall For Inside Track
- Tributaries' T100 and T200 Power Management Solutions
- Tributaries T200 power manager
- tributaries power bar
- Tributaries Launches AC Power Extension Bar