

PWRC-T10X



Description

The Tributaries® T10X Power Extension Bar is designed to provide a maximum 1800W (120V@15A) of clean, filtered and surge suppressed power to audio and video components.

Features

- 10 outlet Power Bar for mounting on rack, on wall or under counter
- 1800 watts / 15 amps
- 3240 joules of surge suppression
- 12 volt trigger in and out
- Line power is filtered to lower the noise floor
- Mounting hardware included
- 3 UL® certifications and RoHS compliant

Specifications

AC OUTLETS

| | |
|-------------------------|-------------------------------------|
| Line Voltage | 120VAC 15A, 50/60Hz |
| Clamping Voltage | 400 Volts |
| Response Time | Instantaneous (>1ns) |
| Surge Current | 400 Amperes |
| Protection Modes | L-N, N-G, L-G |
| Energy Dissipation | 3240 Joules |
| Maximum Spike Current | 6000V |
| Maximum Spike Voltage | 6KV |
| UL®/cUL® Certifications | UL1449, UL1363, UL1283 |
| RoHs Compliant | Yes |
| Power Cord | 15A/14AWG Shielded/45°/3-Prong Plug |

EMI / RFI NOISE FILTERING

| | |
|-------------|-----------------|
| Frequency | 150KHz — 100MHz |
| Attenuation | 70dB |

TRIGGER CIRCUIT

| | |
|----------------|-------------|
| Trigger Inputs | 12VDC |
| Trigger Output | 12VDC |
| Connections | 3.5mm jacks |

PWRC-T10X

PHYSICAL

| | |
|-------------------------|-------------------------|
| Net Weight | 3.8 lbs. (1.7kg) |
| Width | 17" (43cm) |
| Height (including feet) | 1.75" (4.4cm) |
| Depth | 3.25" (8.3cm) |

Notes

While Tributaries® has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Tributaries provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.

Put-Ups

| Stock Code | Description | Color | Quantity |
|-------------------|--|--------------|-----------------|
| PWRC-T10X | 10 Outlet Rack Mount Power Extension Bar | Black | Each |