

PWRI-XF



Description

Featuring 2 outlets, Tributaries® PWRI-XF in-wall AC Power Extension Outlet Kit was designed to work with Tributaries® Power Managers to protect remote displays and projectors. But unlike the standard PWRI-X, the XF has additional filtering to provide noise-free AC at the load end. The inlet and outlet are UL® rated and easy to install into dual or single-gang wall boxes. 14AWG Romex® building wire can then be used to join the inlet and outlet. Kits are available with a 6 foot, 9 foot or 12 foot AC power cable terminated with a Twist-Lock Neutrik® PowerCon® connector that mates with the Neutrik® Twist-Lock PowerCon® inlet.

Features

- Dual outlet In-wall Power Extension Kit with built in additional filtering
- Can be used alone as a filtered outlet without surge suppression or in kit
- Kit is designed to work with a power manager to protect remote devices
- Kit includes 1 filtered power outlet, 1 power inlet and a AC power cable
- Connect the power outlet to the inlet using 14AWG Romex building wire
- Outlet is UL® rated 120 volts / 15 amps for remote installation
- Inlet is UL® rated 120 volts / 15 amps for installation near power manager
- The 14AWG shielded power cable is UL® rated with one end terminated with a Neutrik® PowerCON plug
- Safe hot-pluggable AC connection with Neutrik® PowerCON AC connectors
- Kits are available with your choice of 6 ft., 9 ft. or 12 ft. power cables
- 3 UL® certifications and RoHS compliant

Specifications

Line Voltage	120VAC, 60Hz
Current / Voltage	15Amp / 1800 Watts
Filtering Frequency/Attenuation	150KHz to 100MHz / up to 70dB
AC Power Cord	14AWG shielded
Cord Connectors	Neutrik®NAC3FCA Power connector/NEMA 5-15
AC Outlet	UL® rated
AC Inlet	UL® rated 15A/120V Neutrik® NAC3MPA
UL® Certifications	UL498, UL514
RoHS Compliant	Yes

PWRI-XF

Package Net Weight	1.5 lbs. (kit containing 6 ft. power cable)
Package Width	4.75 in.
Height	4.75 in.
Depth	1.8 in.

Notes

While Tributaries® has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Tributaries provides these specifications on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied.

Put-Ups

Stock Code	Description	Color	Quantity
PWRI-XF-060	In-Wall AC Power Extension Outlet with filter & 6 ft. Power Cable	White	Package
PWRI-XF-090	In-Wall AC Power Extension Outlet with filter & 9 ft. Power Cable	White	Package
PWRI-XF-120	In-Wall AC Power Extension Outlet with filter & 12 ft. Power Cable	White	Package
PWRI-XF-R060	In-Wall AC Power Extension Outlet with filter & 6 ft. Right Angle AC Power Plug	White	Package
PWRI-XF-R090	In-Wall AC Power Extension Outlet with filter & 9 ft. Right Angle AC Power Plug	White	Package
PWRI-XF-R120	In-Wall AC Power Extension Outlet with filter & 12 ft. Right Angle AC Power Plug	White	Package