

SPEAKER CABLES



Plug into
Performance!

Tributaries high performance speaker cables are a unique design by Jay Victor optimized for superior sound quality. Starting with the same conductor criteria as Tributaries audio cables; speaker cable designs incorporate high performance copper with insulated multi-gauge conductors sharing the same sonic traits resulting in a sound which is more frequency balanced.

Special attention to cable geometry is given to the design of speaker cables. Speaker cables carry high current signals that are susceptible to magnetic fields. As a signal travels along a wire it creates a magnetic field that increases with signal voltage. This self-inductance impedes the signal by virtue of its inductive reactance. Star-Quad design cancels magnetic fields and improves the sound quality of your system.

Star-Quad Geometry

Tributaries Series 4, 6 and 8 speaker cables all include a Star-Quad design. Star-Quad speaker cables are designed with four conductors, all wound together, in a "positive, negative, positive, negative" configuration. The cable is produced such that all 4 wires are evenly twisted together keeping each conductor the same distance from the center and ensuring each positive conductor is next to each negative conductor. The net result is the cancellation of opposing electromagnetic fields generated by each conductor pair. This design improves the system's performance by preventing EMI noise from entering and distorting the signals in nearby low level audio, video or digital cables. Another benefit of the Star Quad design is the reduction of the cable's inductance, again, improving the cables electrical performance and reducing the distortion it produces.



Resistance


Resistance is another consideration when choosing a speaker cable. In simple terms: the larger the diameter of the cable or conductor; the lower the resistance. Cable resistance is expressed in ohms per unit. For instance, 500 feet of 16-gauge wire has a resistance of about 4 ohms. With speaker cables this becomes an issue. Because speakers exhibit input impedances in the range of 2 to 8 ohms, the resistance of the cable can add significantly to the overall load. For example, if a 4-ohm speaker is connected to an amplifier with a cable that exhibits a 4-ohm resistance, the cable will dissipate half of the amp's power before it even gets to the speaker! Tributaries offers a full line of speaker wire with gauges from from 11AWG to 16 AWG for your consideration. Below is a handy guide for choosing the correct size speaker wire for your unique installation.

Maximum Wire Lengths for Two Conductor Copper Wire

Wire Size	2 Ω load	4 Ω load	6 Ω load	8 Ω load
16 AWG	12 ft	24 ft	36 ft	48 ft
14 AWG	20 ft	40 ft	60 ft	80 ft
12 AWG	30 ft	60 ft	90 ft	120 ft
10 AWG	50 ft	100 ft	150 ft	200 ft

SPEAKER CABLES

In Bi-wiring, two pairs of speaker cables are run from the same channel of an amplifier to a speaker. The cable design is 2 conductors to 4 conductors. One pair will connect to the high-frequency input and the other to the low frequency input of a speaker. Tributaries Star-Quad Bi-Wire cables are made with 2 pairs of speaker cable in one overall jacket. The cables are arranged in an alternating positive, negative, positive, negative order. The star quad configuration has been designed to reduce noise from Electromagnetic Interference (EMI), minimize the cable's inductance, improve the cable's electrical performance, and decrease distortion. With a lower noise floor - you can hear details in the sound that were previously dulled. Tributaries Bi-Wire Cables are sold in each.



SERIES 6 STAR-QUAD BI-WIRE SPEAKER CABLE

MODEL 6 BW

Professional Grade Speaker Cable

All Series 6 audio cables are meticulously assembled by hand in Orlando, Florida. Series 6 Bi-Wire Speaker cables begin with ultra-pure highly conductive oxygen-free copper (HC-OFC) developed specifically for audio applications. Conductors consist of multiple solid gauges that are mathematically and tonally chosen to support low, mid and high frequencies for a natural sounding cable. Individually insulating each conductor yields zero strand interaction and better sound quality. It is important to understand that music passing through the speaker cable, is actually an AC voltage, so when voltage passes through twisted wire, there will be additional magnetic fields. Tributaries Star-Quad design not only alternates the positive and negative signal conductors but also alternates the twisted lays in each multi-gauge conductor. Alternating lays cancels all levels of magnetic distortion. The end result is a neutral sounding cable

The Series 6 Star-Quad Bi-Wire Speaker cable is stocked in each in lengths from 4 foot to 12 foot lengths with custom lengths available. Available terminated with Spade Lugs or Spring Clip banana plugs

Model 6BW Highlights

- Hand crafted by skilled artisans in Orlando Florida, USA
- Star-Quad design reduces cable inductance and distortion
- Four 14 AWG HC-OFC conductors for best signal transfer
- Sophisticated multi-gauge design for superior bass, mids & highs
- Insulated solid conductor eliminates distortion with stranded bundles
- Unique design by Jay Victor for superior sound quality , exclusively for Tributaries
- Decorative woven jacket over a UL® CL2 PVC jacket

"I could sense the "woodiness" of the guitar and the clarity of Johnson's fingers' friction on the strings, the audible detail was astonishing!"



Mary V. | Audio Enthusiast, Florida