

AUDIO CABLES

We are cable performance.

Tributaries complete line of audio, speaker and power cables were developed exclusively for Tributaries by celebrated cable designer Jay Victor. Using some of the same design principles from Clarus Audiophile cables, it took 3 years to complete the engineering and cosmetic design to offer this comprehensive family of cables to the market.

Tributaries cables incorporate a host of patented technologies. Beginning with copper made specifically for audio applications; conductors are multi-gauge in design with individually insulated strands and precision impedances. The Tributaries collection is complemented by painstakingly meticulous hand-craftsmanship.

Copper

One of the most important considerations in developing audio cables is the grade of copper. Typical high quality electrical grade copper has a purity level of 2N and approximately 1500 crystal per foot. Signals crossing thru these crystal boundaries result in loss and distortion. The next level above this is oxygen-free copper (OFC), the purity of OFC varies. Tributaries uses 2 grades: 3N OFC and a high-conductivity oxygen-free copper (HC-OFC) with 4N of purity. Both are extruded in an oxygen free environment resulting in only 400 crystals per foot. Series 8 cables use copper with purity of 5N called "linear-crystal" copper (LC-OFC). LC-OFC is carefully drawn to produce only 70 crystals per foot, a vast improvement resulting in less loss and distortion.



The Expert in Cable Design

Jay Victor, The engineer behind the development of the Tributaries Audio, Power and Speaker Cables, is a holder of approximately 50 patents for cable geometry. "I am a musician and a life-long music fanatic. Being a technically-minded person, and an Engineer, it is inevitable that Hi-Fi equipment would become a major preoccupation. If music is a major value in your life, then the realistic reproduction of it becomes an obsession. This is what goes into the cables that I design; a relentless pursuit of perfection in reproducing the sound of real music."

Insulated Multi-Gauge Conductors


Tributaries uses solid conductors in its audio cable design. Although stranded cables are valued for their flexibility, the signal can jump from strand to strand in an undesirable manner causing distortion. Another undesirable effect is oxidation which can quickly spread between strands and cause a diode effect impeding signal flow. Conductor size also has an influence on sound. Large conductors transmit signals with less resistance than smaller ones and will also more accurately reproduce the lower frequencies; medium gauge conductors, the mid-frequencies; and fine gauge conductors the high frequencies. Most theories cite skin effect and flux density as reasons for this phenomenon. Further, insulating gauges from one another result in greater clarity.

Cable Geometry

Tributaries audio cables use a twinaxial design. Twinaxial cables have two equally balanced conductors precision twisted and surrounded by a shield. Conductors are insulated using Polyethylene. Polyethylene is chosen because its transparency is similar to Teflon but without the harshness in the high frequencies. Polyethylene is flexible and has a sound quality that is warm and balanced. The shields have 360° coverage to keep noise from entering the signal path. Series 6 and 8 cables include copper braided shields with lower resistance for trapping induced noise current. In this design the signal and return have dedicated separate conductors and the shield is free to be connected at the source end only eliminating EMI & RFI induced noise from entering the receiver. The best balanced cables are triple balanced with three equally balanced twisted conductors surrounded by a shield. In a balanced system using dedicated conductors for the positive, negative and ground with an additional shield connected only at the source end delivers audible improvements by lowering the noise allowing you will hear more of the recorded music

AUDIO CABLES

Phono cables are designed to connect a turntable or tonearm to a separate phono stage or phono input of a preamplifier. Phono cables are particularly important audio cables because low level output from the phono cartridge is very precise but also very fragile. All Tributaries phono preamp cables have a separate ground wire to eliminate low level humms caused by ground loops.



SERIES 6 PHONO PREAMP CABLE SET

MODEL: 6PC

Professional Level Audio cable

All Series 6 phono cables are meticulously assembled by hand in Orlando, Florida. The Series 6 phono cable set is comprised of a S6 Single-Ended RCA audio cable and ground wire. The Series 6 audio cables begin with ultra-pure highly conductive oxygen free copper (HC-OFC) developed specifically for audio applications. Each conductor is engineered with dual solid gauge wires that are mathematically and tonally chosen to support low, mid and high frequencies for a natural sounding cable. Individually insulating each wire yields zero strand interaction and better sound quality. Unbalanced analog audio systems will benefit from using Tributaries Twin-Axial cable design. The precision twisted Twin-Axial design has dedicated conductors for the positive signal and negative return signal plus a heavy shield that is connected to the source end only. In this design the shield will capture any induced interference sending it to ground at the source end thereby isolating noise away from the input stage of the load. The ground wire is a flexible 20AWG stranded wire terminated with a gold plated spade lug that will fit ground posts that are 4mm and smaller. This configuration ensures a clear signal transfer with overall noise rejection as close to balanced as possible. The end result is a neutral sounding cable.

The Series 6 Phono cable set is stocked as an RCA pair plus one ground wire. Phono cable sets are available in 1/2 meter to 4 meter lengths with custom lengths available

Model 6PC Highlights

Hand crafted by skilled artisans in Orlando Florida, USA
Precision-Twisted Twin-Axial 20AWG HC-OFC conductors
Sophisticated multi-gauge design for Superior bass & midrange
Insulated conductors eliminate strand interaction/distortion
Dual shielded to lower the noise floor
Gold-plated solid-brass RCA connectors
Decorative woven jacket over a UL® CL2 PVC jacket
20AWG stranded ground wire terminated with gold-plated spade lugs
Grounding spade lug fit 4.0mm or smaller ground posts
Available in custom lengths either pairs or mono cables